



IOTRON™ SENSORS

INTEGRATED INDUSTRIAL ORP SENSOR SPECIFICATIONS

<u>Sensor Part Number & Short Description:</u>	6852 – Oxidation Reduction Potential (ORP) Sensor for Inline Use with ¾” MNPT Front Threads and Immersion/Submersion Type Installations with 1” MNPT Rear Threads
<u>Configuration Type:</u>	<i>Interface with ¾” FNPT threads of tee or process tank for Inline Use or 1” FNPT threads on insertion tube for immersion or waterproofing seal for submersible installations</i>
<u>General Sensor Specifications:</u>	
Operating Temperature Range:	-5 to 70°C
Operating Pressure Range:	1 to 100 psig (6.9 to 690 kPa) with ¾” MNPT Front Threads for Inline Installations
Sensor Body Material:	RYTON® R-4-230BL (Poly-Phenylene-Sulfone, PPS)
Junction Support Matrix Material:	High-Density Polyethylene (HDPE)
External Dimensions:	See Drawing 6-1-Pt
<u>ORP Measurement Specifications:</u>	
Measurement mV Range:	-2,000 to +2,000 mV absolute
Measuring Glass Type:	Platinum Ball in Low Profile Configuration; Suitable for Slurries & High Pressure/Velocity
pH Glass Dimensions:	0.197” (5.0 mm) DIA
<u>Reference System Specifications:</u>	
Type:	Double Junction Standard (Triple Junction Optional, Alpha Prefix “TJ”)
Reference Half Cell:	Ag/AgCl, Saturated KCl
Primary Junction:	Porous Ceramic, Sat. KCl in crosslinked polymer, Interfaced to Secondary Junction
Secondary Junction:	Solid-State Non-Porous Cross-Linked Polymer embedded in HDPE Support Matrix holds excess KCl assuring saturation at all temps for stability & long sensor service life
<u>Supported Order Options with Alpha Prefix Order Code Designation:</u>	Ammonia gas resistant (“A”), Organic Media Resistant (“L”), Solvent Resistant (“TS”), 3-Wire TC (“M”), ACCU-TEMP Fast TC (“X”), Reduce to 2 ea Protective Tines (“GRO”), No Protective Tines (“NG”), Shielded Preamp Cable (“BL”)
<i>Inquire to factory for specials</i>	
<u>Example Recommended Applications:</u>	Any process media where the redox (ORP) potential is monitored or controlled. Can be combined with other sensor options available for pH sensors such as high temperature resistant, slurry & viscous material resistant, acid fluoride & HF resistant, pulp and paper resistant, sulfide resistant, dissolved gas and organic solvent resistant or saturated brine resistant. Any measurement where aggressive chemical cleaning is needed to remove fouling or low-maintenance operation is required with minimal cleaning and re-calibration.
<u>Storage and Shelf Life:</u>	One (1) year from date of dispatch from factory when stored at indoor ambient room temperature with proper orientation & protector cap.
<u>Available Configurations & Options:</u>	
Integrated Components:	<ul style="list-style-type: none">- Temperature Compensation Element (compatible type must be specified)- Solution Ground Liquid Earth, 316SS (alpha prefix “Y”), or Platinum (alpha prefix “Pt”)- Analog Conventional or Differential Preamplifier (Contact factory for available options)- Smart digital sensor board for use with 3TX-HiQ-pH Intelligent pH & ORP transmitters
Analog Sensors without integral preamplifier:	Terminated with Male BNC connector (-MBNC) or Tinned Lead Wires (-TL)
Analog Sensors with integral preamplifier:	Terminated with Tinned Lead Wires (-TL) or Quick Disconnect NEMA 6P Snap (-Q7M)
Digital Smart Sensors:	Terminated standard with quick disconnect IP67/NEMA 6P rated waterproof & corrosion resistant snap HiQ4M connector. For 3TX-HiQ-pH Intelligent pH & ORP transmitters or HiQDT style with RS-485 MODBUS RTU to interface with any suitable PLC or SCADA (Minimum Order Quantity may apply for HiQDT style version, contact factory for details)

1

2

3

REVISION HISTORY		
REV	DESCRIPTION	DATE

DESCRIPTION

DATE

APPROVED


Platinum Low-Profile Ball
Sealed into glass for
ORP Sensing Element

3/4" - 14 NPT

0.875"
DIA.

FLATS FOR
1 1/16" WRENCH

1" - 11.5 NPT
1.31" DIA MAX



A

A

NOTES

- All dimensions are in inches, unless otherwise indicated with tolerances as detailed below
- Sensor body material of construction is RADEL (6X31), PEEK (6X41) or RYTON (6X51, 6X52)
- Drawing shown in the standard with protective tines configuration (4 places, 90 degrees apart).
The 2 protective tines only "GRO" configuration (2 places, 180 degrees apart) is optional.
- In the alternate without tines configuration ("NG") the sensor body is exactly 8.0 inches in length.
The max displacement for ORP sensing element is 0.1" yielding a max insertion depth of 1.6 inches past threads & overall max length of 8.1 inches.
- Do not use any sensor beyond the factory defined maximum temperature or pressure rating.

B

B



Advanced Sensor Technologies U.S.A.
Website: <http://www.astisensor.com>

TITLE		3/4"-1" MNPT Inline / Immersion / Submersible	
SIZE	PROJECT	DRAWING NO.	REV
B	IMMERSION	6-1-Pt Low-Profile ORP	/
SCALE		MODEL	SHEET
Not to Scale		6X31,6X41,6X51,6X52	1 OF 1

TOLERANCES

1 Place: ± .1	3 Places: ± .005	DRAWN BY	RH
2 Places: ± .01	4 Places: ± .0005	CHECKED BY	TADP
Angular: ± 0.25°		APPROVED BY	MJP

1

2

3